

GZZ XR2 P7" Driving light LED - White

Experience the power of light with OZZ XR2 P7". These 178 mm lights feature a dynamic start-up position light in white and orange. The innovative successor to the original OZZ light series offers a new prominent start-up pattern for an impressive visual effect upon ignition. With a boost function, the OZZ XR2 P7" emits 5800 lumen, providing 1 lux at a distance of 470 meters. The driving beam pattern ensures optimal visibility with a wide and long-range reach. The lights have a color temperature of 5000 K, offering pleasant illumination in all conditions.

Art. no.	88104	Material bracket	Stainless steel
Pcs LED	16	Material housing	Aluminum
Voltage	12-35V DC	Material lens	Polycarbonate
Theoretical effect	80W	Lenght (mm)	178
Actual effect	78W (12V DC), 75,6W (24V DC)	Depth (mm)	72
Nominal current	6,5A (12V DC), 3,15A (24V DC)	Height (mm)	170
Functions	High beam, Dynamic position light	Height including bracket (mm)	186
Theoretical lumen	7200	Diameter (mm)	178
Actual lumen	5800	CC (mm)	-
1 lux @	470 m	Operating temperature	-40°C - +60°C
Kelvin	5000K	E-mark approval	ECE R148, R149
IP-class	IP68/IP69K	Reference number	50
Beam pattern	Driving	EMC	ECE R10
Position light	Dynamic white and amber	Pcs in master box	6
Color housing	White	EAN	7333213101466
RAL color	RAL9003	Warranty	3 years
Color lens	Clear		
Color LED	White, amber		
Connection	4-pin DT male + female		
Cable lenght (mm)	1000 (800+200)		



